METAL FORM MANUFACTURING CO., INC
5960 WEST WASHINGTON STREET
PHOENIX, ARIZONA 85043
TELEPHONE: 602-233-1211 FAX: 602-233-2033
WEBSITE ADDRESS: WWW.MFMCA.COM

Model MFA-16 Extruded Aluminum Stationary Louver

4" Deep Drainable Blade

Specifications

Frame:	.090" 6063-T5 extruded aluminum channel frame.
Blades:	.081" 6063-T5 extruded aluminum.
Screen:	1/2" x .051" flattened expanded aluminum.
Finish:	Standard mill.
Minimum size:	12"w x 12"h.
Maximum size:	72"w x 120"h. Multiple section - unlimited size.



Section View


Mullion Detail



Optional Flanged Frame

Options

-Flanged frame.
-Architectural mullions.
-Sill extension.
-Sleeves.
-Sub frame (requires flanged louver).
-Screens - Many variations of screens are available, consult factory.
-Finishes - Many types of finishes are available, consult factory.
-Other options available, consult factory.

Notes

1. Width x height are nominal opening dimensions. Unless specified otherwise, units will be constructed 1/4" undersize.
2. Metal Form reserves the right to improve design or change specifications at any time.

Model MFA-16 is AMCA licensed for air performance and water penetration.

Tag	Qty.	Width	Height	No. of Panels (W x H)	Options	Finishes/Specify	Remarks

Project: _____
Architect: _____
Engineer: _____
Contractor: _____

Metal Form Manufacturing Co., Inc.
Form No. A-1611 © November 2011
Supercedes Form No. A-1698

Refer to back page for performance data.

Model MFA-16
Performance Data

Air Performance



Water Penetration



The beginning of water penetration is 732 FPM
(15 min. duration)

Test unit size 48" x 48"
Graphs are corrected to standard air density .075 lbs. per cubic feet.
Ratings do not include the effects of a bird screen.

Free Area Chart - Sq. Ft.

Height	Width										
	12	18	24	30	36	42	48	54	60	66	72
120	4.63	7.34	10.05	12.76	15.47	18.18	20.90	23.61	26.32	29.03	31.74
108	4.10	6.50	8.90	11.30	13.69	16.09	18.49	20.89	23.29	25.69	28.09
96	3.50	5.71	7.92	10.13	12.34	14.55	16.75	18.96	21.17	23.38	25.59
84	2.97	4.85	6.72	8.60	10.47	12.35	14.23	16.10	17.98	19.85	21.73
72	2.57	4.20	5.83	7.45	9.08	10.70	12.33	13.96	15.58	17.21	18.83
66	2.31	3.77	5.23	6.69	8.15	9.61	11.07	12.53	13.99	15.45	16.90
60	2.06	3.36	4.67	5.97	7.27	8.57	9.87	11.18	12.48	13.78	15.08
54	1.88	3.07	4.26	5.44	6.63	7.82	9.00	10.19	11.38	12.57	13.76
48	1.65	2.69	3.74	4.78	5.82	6.86	7.91	8.95	9.99	11.04	12.08
42	1.39	2.26	3.14	4.02	4.89	5.77	6.64	7.52	8.40	9.27	10.15
36	1.15	1.88	2.61	3.34	4.07	4.80	5.53	6.26	6.99	7.72	8.45
30	0.97	1.59	2.20	2.82	3.43	4.05	4.66	5.28	5.89	6.50	7.12
24	0.73	1.19	1.65	2.11	2.56	3.02	3.48	3.94	4.40	4.86	5.32
18	0.46	0.76	1.05	1.34	1.63	1.93	2.22	2.51	2.81	3.10	3.39
12	0.25	0.40	0.56	0.72	0.87	1.03	1.18	1.34	1.50	1.65	1.81

amca CERTIFIED RATINGS
WATER PENETRATION
AIR PERFORMANCE
AIR MOVEMENT AND CONTROL ASSOCIATION INTERNATIONAL, INC.

Metal Form certifies that the Model MFA-16 shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to air performance ratings and water penetration ratings.