



Section View

Standard Specifications

- Perimeter Frame:** 2" x 1/8" HR Flat Bar, corners continuously welded
- Horizontal Bars:** 1" x 1/8" HR Flat Bar, approximately 12" OC, continuously welded to perimeter frame.
- Vertical Bars:** 1/2" diameter HR round bars, approximately 6" OC, continuously welded to perimeter frame.
- Finish:** One coat MFM "Grey" primer
- Min. & Max Size:** 6" x 6" to 96" x 96" – Attach multiple sections to form larger sizes

Options

- Shape:** Circular, Flat Oval
- Perimeter Frame:** 2" x 1/4", 2-1/2" x 1/4", 3" x 1/4", 4" x 1/4", 2" x 3/8", 2-1/2" x 3/8", 3" x 3/8", 4" x 3/8"
- Horizontal Bars:** HR or CR Steel, 1/4" or 3/8" thickness, 1-1/2", 2" or 2-1/2" width
- Horizontal Spacing:** 3" to 12" On Center
- Vertical Bars:** HR Steel - 5/8", 3/4", 7/8" or 1" diameter
 CR Steel - 5/8", 3/4", 7/8" or 1" diameter
- Vertical Spacing:** 3" to 12" On Center
- Finish:** Epoxy Enamel or Thermal-setting Powder Coat, Color to be selected.

SCHEDULE

Tag	Qty	Width or Diameter	Height	Vertical Bar Size & Spacing	Horizontal Bar Size & Spacing	Finish	Remarks

Note: Width x Height are nominal opening dimensions. Unless specified otherwise, units will be constructed 1/4" less.

Project: _____
 Architect: _____
 Engineer: _____
 Contractor: _____